



High Contrast Imaging Testbed

Andrew E. Lowman, John T. Trauger, Brian Gordon,
Joseph J. Green, Dwight Moody, Albert F. Niessner, Fang Shi

Jet Propulsion Laboratory, California Institute of Technology

TPF Science, Technology, and Design Expo

15 October 2003



HCIT Objectives



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission

- Laboratory validation of coronagraph technology
 - Wavefront Sensing and Control
 - Measure and correct amplitude and phase errors
 - Deformable mirror performance
 - Masks and Stops
 - End-to-end coronagraph performance
 - Modeling
 - Component characterization
 - Stray light suppression
- Demonstration of coronagraph flight readiness
 - Deterministic achievement of testbed goals
 - Test elements of TPF coronagraph error budget




Current Testbed Layout



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission







Testbed in Vacuum



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission






Baseline WFS (MGS) Repeatability



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission





Baseline WFS (MGS) Repeatability II




Terrestrial Planet Finder Mission


TPF

A NASA
Origins
Mission

Average Estimate



Standard Deviation within 15 Cycles/Pupil






Baseline WFS Model Match




Terrestrial Planet Finder Mission

TPF

OPD From Diffraction Model



Difference from Diffraction Model



$\lambda/200$ rms agreement...enviable for traditional telescope, not for TPF

A NASA
Origins
Mission




Drift in Camera Focus



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission






Baseline Performance (Flat) in Vacuum



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission







32x32 Deformable Mirror “Gen 2”



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission



- Received two DM's from Xinetics
- Fully functional
- Actuation limited at edges
 - Reduced aperture 10%



32x32 DM Performance




Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission

- Optical characterization in surface gauge
 - Michelson interferometer in vacuum, located beneath HCIT bench
- Sparse patterns applied to measure gains
- Wavefront flattened iteratively
 - Final surface figure (in controllable band) 1.5\AA rms over 25×25 area
- DM integrated into HCIT






Contrast Measurement



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission






Contrast Contour Plot



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission





DM/MUX Development Status



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission

- 64x64 DM development at Xinetics
 - DM currently in coating
 - Delivery expected 10/30
- MUX development
 - Needed to drive 64x64 DM
 - JPL-designed 64 channel low power, high voltage ASIC
 - Currently fabricating boards, testing packaged chips



Component Characterization



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission

- Component performance critical to testbed success
 - DM
 - Optical figure
 - Coatings
 - Fiber
 - How to make a star without artifacts
 - Masks and Stops
 - Both amplitude and phase impact performance
 - TPF is developing lab instrumentation to measure both



Guest Testing on HCIT



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission

- Masks and Stops
 - Both Lyot and apodized coronagraph concepts
- Modeling
- Telescope Front End
 - Hardware simulation of relevant TPF telescope
 - Star field and planet simulator
- Possibilities:
 - Nuller
 - Other hardware



Acknowledgment



Terrestrial Planet Finder Mission

TPF

A NASA
Origins
Mission

This research was carried out at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration.